

HIVIDEO



▲ **SPECIFICATION** www.hivideocctv.com "Reliable Digital Security Products Manufacturer"

Model NO.	HI-88CIP5A
Camera SPEC	
Pixels	4.0 Mega Pixel
Image Sensor	GC5653
Main processor	FH8852V200
Effective Pixels	2500*1600P
TV System	PAL/NTSC
Main stream	(2500*1660)/3MP(2304*1296)/2MP(1920*1080)/1MP(1280*720)
Sub-stream	448P(800*448)/D1(704*576)/360P(640*360)/ CIF(352*288)
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
Usable Illumination	0.01Lux
S/N Ratio	≥52dB
Video Output	Network
Network	
Ethernet	RJ-45 (10/100M)
Protocol	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, IP Search
Protocol optional	ONVIF2.4 / Hikvision
P2P	Support
POE	Support
WIFI	N/A
Video Delay	0.3S (Within the Lan)
Smart Phone	iPhone, iPad, Android, Android Pad
Frames Per Second	25Fps
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/H.265
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Motion Detection	Support
Privacy Masking	3 Rectangular Zone

DWDR / WDR	DWDR
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German,Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian
Audio	G.711
Lens	
Focus Length	3.6mm / 2.8mm Lens
Focus Control	Fixed
Lens Type	Fixed
Night Vision	
Infrared LED	3PCS SMT LED
Infrared Distance	35M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
General	
Housing	Metal
Bracket	YES
IR Cut Filter	YES
Operation Temperature	-10℃ ~ +50℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	204.28*64.61*69*17mm
Weight	0.6kg