

## ZJ-8370 / POS-8370 Specification

### Specifications

Print Method	Direct Line Thermal
Interfaces	USB / LAN / Bluetooth (optional)
Print Comand	ESC / POS command
Print Speed	220mm/s
Resolution	203DPI (8dot/mm)
TPH Reliability	100km
Auto Cutter	Partial
Cutter Life	1.0 million cuts
Logo	support downloading and printing logo
Line Spacing	3.75mm (Adjustable by commands)
Extension Character Sheet	PC437 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian) 、PC865 (Nordic) 、West Europe、Greek 、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、Thai、PT151 (1251)
Character Size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese, Traditional Chinese:3.0×3.0mm (24×24 dots)
Supported Code:	1D: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
Input Buffer	96K bytes
NV Flash	256K bytes
Driver	Win2003 / WinXP / Win7 / WIN8 / WIN10 / Linux ; Support IOS / Android
Power	Input: AC 110V/220V, 50~60Hz ; Output: DC 24V/1.5A

### Paper

Paper Types	Thermal Roll Paper
Paper Width	79.5±0.5mm / φ 80 mm
Print Width	72mm
Paper Thickness	0.06-0.08 mm

### Package

Printer Dimension	17.47*14.17*12.23cm
Printer N.W.	0.84 kg
Package	1pc with accessories/Box, 12 boxes/CTN
Accessories	Manual, USB Cable, Power Adapter, Paper Roll
Box Dimension	20.3*18.6*13.9 CM
Box G.W.	1.22 Kgs
CTN Dimension	61.4*38.8*29.8 CM
CTN G.W.	15Kgs

### Environmental Requirements

Work Environment	Temperature (0~45℃) humidity(10~80%)
Storage Environment	Temperature(-10~60℃) humidity(10~90%)
Mechanical Noise	less than 60dB